

# J. K. STEEL STRIPS LLP

## SPECIFICATIONS FOR Electrogalvanised Steel

### Grades :

Symbol	Thickness (mm)	Base Metal	Grade
SECC	0.3 -3.0	SPCC	Commercial
SECD		SPCD	Drawing
SECE		SPCE	Deep Drawing

### Mechanical Properties :

Symbol	Yield Strength N/mm <sup>2</sup>	Tensile Strength N/mm <sup>2</sup>	Elongation (%)			
			Thickness (mm)			
			0.3 ≤ < 0.6	0.6 ≤ < 1.0	1.0 ≤ < 1.6	1.6 ≤ < 3.0
SECC	-	270 min	34 min	36 min	37 min	38 min
SECD	-	270 min	36 min	38 min	39 min	40 min
SECE	-	270 min	38 min	40 min	41 min	42 min

### Electrogalvanised Steel:

- **Width Thickness: 0.3 – 3.0mm**
- **Coating Layer: Pune Zinc Coating**
- **Coil Weight: 5MT – 20MT ID 508mm**
- **Coil Width: 700 – 1250mm**

Address: 11<sup>th</sup> Floor, 1130, Hubtown Solaris,  
N. S. Phadke Marg, Opp. Telli Galli,  
Andheri(E), Mumbai-400069, INDIA.

Tel: +91-022-26837310 / 26820282

Mobile: +91-9769 111 043

Email: mkt@doshienterprises.com